











安装信息请参考我们的工具选型  
及我们网站上 [www.rivettech.cn](http://www.rivettech.cn) 安  
装工具与系统栏目。

- 坚固低成本紧固件。
- 是大范围应用的理想选择。
- 能应对通用紧固件的需求
- 可适用一定范围内的尺寸和材质。

铆钉直径	(L) 铆体长度	(F) 盲端突出	 夹紧厚度	铆钉零件编号	 孔大小	 抗剪力	 抗拉力	
In. (mm)	In. (mm)	In. (mm)	In. (mm)		In. (mm)	Lbs. (N)	Lbs. (N)	
<b>5052 铝体/铝芯轴-120° 沉头-表面处理: 本色处理/本色处理</b>								
1/8 (3.2)	.250 (6.5)	.370 (9.4)	.063-.125 (1.6-3.2)	AK 42 ABS	.129-.133 (3.30-3.40)		155 (689)	235 (1045)
	.313 (8.0)	.433 (11.0)	.126-.187 (3.2-4.8)	AK 43 ABS				
	.375 (9.5)	.495 (12.6)	.188-.250 (4.8-6.4)	AK 44 ABS				
	.438 (11.1)	.558 (14.2)	.251-.312 (6.4-7.9)	AK 45 ABS				
	.500 (12.7)	.620 (15.7)	.313-.375 (7.9-9.5)	AK 46 ABS				
	.750 (19.1)	.870 (22.1)	.501-.625 (12.8-15.9)	AK 410 ABS				
5/32 (4.0)	.275 (7.0)	.415 (10.5)	.063-.125 (1.6-3.2)	AK 52 ABS	.160-.164 (4.06-4.17)		225 (1000)	350 (1556)
	.400 (10.2)	.540 (13.7)	.188-.250 (4.8-6.4)	AK 54 ABS				
	.525 (13.3)	.665 (16.9)	.313-.375 (7.9-9.5)	AK 56 ABS				
3/16 (4.8)	1.175 (29.9)	1.335 (33.9)	.876-1.00 (22.2-25.4)	AK 616 ABS	.192-.196 (4.88-4.98)		315 (1401)	500 (2224)
(3.2)	.188 (4.8)	.308 (7.8)	.032-.062 (.8-1.6)	AD 41 BS	.129-.133 (3.30-3.40)		210 (934)	325 (1445)
	.250 (6.5)	.370 (9.4)	.063-.125 (1.6-3.2)	AD 42 BS				
	.313 (8.0)	.433 (11.0)	.126-.187 (3.2-4.8)	AD 43 BS				
	.375 (9.5)	.495 (12.6)	.188-.250 (4.8-6.5)	AD 44 BS				
	.438 (11.1)	.558 (14.2)	.251-.312 (6.5-7.9)	AD 45 BS				
	.500 (12.7)	.620 (15.7)	.313-.375 (7.9-9.5)	AD 46 BS				
	.625 (15.9)	.745 (18.9)	.376-.500 (9.5-12.7)	AD 48 BS				
	.750 (19.1)	.870 (22.1)	.501-.625 (12.8-15.9)	AD 410 BS				