



安装信息请参考我们的工具选型及我们网站上 www.rivettech.cn 安装工具与系统栏目。



铆体: 铝 AlMg3
钉芯: 钢, 镀锌

(圆头)

	铆体 D ₁ x L mm	铆接范围 mm	编号	每盒数量
2,4 孔径 Ø: 2,5 mm	2,4 x 4	0,5 - 1,5	630 0014	A 1.000
	2,4 x 6	1,5 - 3,5	630 0022	"
	2,4 x 8	3,5 - 5,0	630 0030	"
3 孔径 Ø: 3,1 mm	3 x 4	0,5 - 1,5	630 0103	A 500
	3 x 5	1,5 - 2,5	630 0111	"
	3 x 6	2,5 - 3,5	630 0138	"
	3 x 7	3,5 - 4,5	630 0146	"
	3 x 8	4,5 - 5,0	630 0154	"
	3 x 10	5,0 - 7,0	630 0162	"
	3 x 12	7,0 - 9,0	630 0170	"
	3 x 14	9,0 - 11,0	630 0189	"
	3 x 16	11,0 - 13,0	630 0197	"
	3 x 18	13,0 - 15,0	630 0200	A 250
	3 x 20	15,0 - 17,0	630 0219	"
	3 x 25	17,0 - 22,0	630 0227	"
	3 x 30	22,0 - 26,0	630 0235	"
3,2 孔径 Ø: 3,3 mm	3,2 x 4	0,5 - 1,5	630 0308	A 500
	3,2 x 6	1,5 - 3,5	630 0316	"
	3,2 x 8	3,5 - 5,0	630 0324	"
	3,2 x 10	5,0 - 7,0	630 0332	"
	3,2 x 12	7,0 - 9,0	630 0340	"
	3,2 x 14	9,0 - 11,0	630 0081	"
	3,2 x 16	11,0 - 13,0	630 0359	B 500
	3,2 x 18	13,0 - 15,0	630 0383	"
	3,2 x 20	15,0 - 17,0	630 0367	"
	3,2 x 25	17,0 - 22,0	630 0375	"

	铆体 D ₁ x L mm	铆接范围 mm	编号	每盒数量
4 孔径 Ø: 4,1 mm	4 x 5	0,5 - 1,5	630 0405	A 500
	4 x 6	1,5 - 3,0	630 0413	"
	4 x 7	3,0 - 4,0	630 0421	"
	4 x 8	4,0 - 5,0	630 0448	"
	4 x 10	5,0 - 6,5	630 0456	"
	4 x 12	6,5 - 8,5	630 0464	B 500
	4 x 14	8,5 - 10,5	630 0472	"
	4 x 16	10,5 - 12,5	630 0480	"
	4 x 18	12,5 - 14,5	630 0499	"
	4 x 20	14,5 - 16,5	630 0502	"
	4 x 25	16,5 - 21,5	630 0529	"
	4 x 30	21,5 - 26,0	630 0545	B 250
	4 x 35	26,0 - 30,0	630 0561	"
4,8 孔径 Ø: 4,9 mm	4,8 x 6	2,0 - 2,5	630 0707	B 500
	4,8 x 8	2,5 - 4,5	630 0715	"
	4,8 x 10	4,5 - 6,0	630 0723	"
	4,8 x 12	6,0 - 8,0	630 0731	"
	4,8 x 14	8,0 - 10,0	630 0758	"
	4,8 x 16	10,0 - 12,0	630 0766	"
	4,8 x 18	12,0 - 14,0	630 0774	"
	4,8 x 20	14,0 - 15,0	630 0782	B 250
	4,8 x 25	15,0 - 20,0	630 0804	"
	4,8 x 30	20,0 - 25,0	630 0820	A 100

铆钉直径 \emptyset mm	抗剪力		抗拉力		钉芯 \emptyset mm	最大帽檐 \emptyset mm
	N	(kp)	N	(kp)		
2,4	350	(35)	450	(46)	1,5	5,0
3	700	(71)	900	(92)	1,8	6,5
3,2	720	(73)	950	(97)	1,95	6,5
4 x 5-25	1.400	(143)	2.000	(204)	2,1	8,0
4 x 30-40 ⁿ	850	(87)	1.000	(102)	2,1	8,0
4,8	1.800	(184)	2.700	(275)	2,7	9,5

ⁿ 铆体: AlMgSi

测试程序按照 DIN EN ISO 14589 标准

色彩图例



作为德国GESIPA® 中国区重要合作伙伴, 我们愿携手GESIPA® 公司共同为中国区客户提供高质量铆接解决方案。



安装信息请参考我们的工具选型及我们网站上 www.rivettech.cn 安装工具与系统栏目。



铆体: 铝 ALMg3
钉芯: 钢, 镀锌

(圆头)

	铆体 D ₁ x L mm	铆接范围 mm	编号	每盒数量
5 孔径 Ø: 5,1 mm	5 x 6	2,0 - 2,5	630 0901	B 500
	5 x 8	2,5 - 4,5	630 0928	"
	5 x 10	4,5 - 6,0	630 0936	"
	5 x 12	6,0 - 8,0	630 0944	"
	5 x 14	8,0 - 10,0	630 0952	"
	5 x 16	10,0 - 12,0	630 0960	"
	5 x 18	12,0 - 14,0	630 0979	"
	5 x 20	14,0 - 15,0	630 0987	B 250
	5 x 25	15,0 - 20,0	630 1002	"
	5 x 30	20,0 - 25,0	630 1029	A 100
	5 x 35	25,0 - 30,0	630 1045	"
	5 x 40	30,0 - 35,0	630 1061	"
	5 x 45	35,0 - 40,0	630 1096	B 100
	5 x 50	40,0 - 45,0	630 1126	"
	5 x 55	45,0 - 48,0	630 1142	"
	5 x 60	48,0 - 52,0	630 1169	"
5 x 65	52,0 - 57,0	630 1185	"	
5 x 70	57,0 - 62,0	630 1207	"	
5 x 80	62,0 - 72,0	630 1223	"	

	铆体 D ₁ x L mm	铆接范围 mm	编号	每盒数量
6 孔径 Ø: 6,1 mm	6 x 8	2,0 - 3,0	630 1304	B 250
	6 x 10	3,0 - 5,0	630 1312	"
	6 x 12	5,0 - 7,0	630 1320	"
	6 x 16	7,0 - 11,0	630 1339	"
	6 x 18	11,0 - 13,0	630 1347	"
	6 x 20	13,0 - 15,0	630 1355	"
	6 x 25	15,0 - 20,0	630 1371	B 200
	6 x 30	20,0 - 24,0	630 1401	"
	6 x 35	24,0 - 29,0	630 1436	B 100
	6 x 40	29,0 - 34,0	630 1452	"
6,4 孔径 Ø: 6,5 mm	6,4 x 12	2,0 - 6,0	630 1606	B 250
	6,4 x 16	6,0 - 10,0	630 1622	"
	6,4 x 18	10,0 - 12,0	630 1940	"
	6,4 x 20	12,0 - 14,0	630 1649	B 200
	6,4 x 25	14,0 - 18,0	630 1665	"
	6,4 x 30	18,0 - 23,0	630 1681	B 100

铆钉直径 Ø mm	N	抗剪力 (kp)	N	抗拉力 (kp)	钉芯直径 Ø mm	最大帽檐 Ø mm
5	2.000	(204)	2.800	(285)	2,7	9,5
6	3.100	(316)	3.800	(388)	3,2	12,0
6,4	3.400	(347)	4.600	(469)	3,65	13,0

测试程序按照 DIN EN ISO 14589 标准

色彩图例



铝



钢



铜



A2 不锈钢



蒙乃尔



塑料



A4 不锈钢

作为德国GESIPA[®] 中国区重要合作伙伴，我们愿携手GESIPA[®] 公司共同为中国区客户提供高质量铆接解决方案。