



安装信息请参考我们的工具选型及我们网站上 www.rivettech.cn 安装工具与系统栏目。



铆体: 钢, 镀锌
钉芯: 钢, 镀锌

(圆头)

	铆体 D, x L mm	铆接范围 mm	编号	每盒数量
3 孔径 Ø: 3,1 mm	3 x 5	0,5 - 2,0	631 0117	A 500
	3 x 6	2,0 - 3,0	631 0133	"
	3 x 8	3,0 - 5,0	631 0141	"
	3 x 10	5,0 - 6,5	631 0168	"
	3 x 12	6,5 - 8,5	631 0176	"
	3 x 16	8,5 - 12,5	631 0192	B 500
	3 x 18	12,5 - 14,5	631 0206	"
	3 x 20	14,5 - 16,5	631 0214	"
3,2 孔径 Ø: 3,3 mm	3,2 x 6	0,5 - 3,0	631 0303	A 500
	3,2 x 8	3,0 - 5,0	631 0311	"
	3,2 x 10	5,0 - 6,5	631 0338	"
	3,2 x 12	6,5 - 8,5	631 0346	"
	3,2 x 16	8,5 - 12,5	631 0354	B 500
	3,2 x 18	12,5 - 14,5	631 0249	"
	3,2 x 20	14,5 - 16,5	631 0362	"
4 孔径 Ø: 4,1 mm	4 x 6	0,5 - 2,5	631 0419	A 500
	4 x 8	2,5 - 4,5	631 0443	"
	4 x 10	4,5 - 6,5	631 0451	B 500
	4 x 12	6,5 - 8,5	631 0478	"
	4 x 16	8,5 - 12,0	631 0486	"
	4 x 18	12,0 - 14,0	631 0516	"
	4 x 20	14,0 - 16,0	631 0508	"
4,8 孔径 Ø: 4,9 mm	4,8 x 8	2,0 - 4,0	631 0710	B 500
	4,8 x 10	4,0 - 6,0	631 0729	"
	4,8 x 12	6,0 - 8,0	631 0737	"
	4,8 x 16	8,0 - 11,0	631 0761	"
	4,8 x 20	11,0 - 15,0	631 0788	B 250
	4,8 x 25	15,0 - 20,0	631 0818	"

	铆体 D, x L mm	铆接范围 mm	编号	每盒数量
5 孔径 Ø: 5,1 mm	5 x 8	2,0 - 4,0	631 0915	B 500
	5 x 10	4,0 - 6,0	631 0923	"
	5 x 12	6,0 - 8,0	631 0931	"
	5 x 14	8,0 - 9,5	631 0958	"
	5 x 16	9,5 - 11,0	631 0966	"
	5 x 18	11,0 - 13,0	631 0974	"
	5 x 20	13,0 - 15,0	631 0982	B 250
	5 x 25	15,0 - 20,0	631 1008	"
	5 x 30	20,0 - 25,0	631 1024	A 100
	5 x 35	25,0 - 30,0	631 1040	"
	5 x 40	30,0 - 34,0	631 1067	"
	5 x 45	34,0 - 39,0	631 1091	"
	5 x 50	39,0 - 44,0	631 1121	B 100
6 孔径 Ø: 6,1 mm	6 x 10	2,5 - 4,5	631 1202	B 250
	6 x 12	4,5 - 6,5	631 1210	"
	6 x 14	6,5 - 8,5	631 1229	"
	6 x 16	8,5 - 10,5	631 1237	"
	6 x 20	10,5 - 14,5	631 1245	"
6,4 孔径 Ø: 6,5 mm	6 x 25	14,5 - 19,5	631 1253	"
	6,4 x 8	1,0 - 3,0	631 1598	B 250
	6,4 x 12	3,0 - 6,0	631 1601	"
	6,4 x 16	6,0 - 9,0	631 1628	"
	6,4 x 18	9,0 - 11,0	631 1563	B 200
	6,4 x 20	11,0 - 13,0	631 1644	"
6,4 x 25	13,0 - 17,0	631 1660	"	

铆钉直径 Ø mm	抗剪力		抗拉力		钉芯直径 Ø mm	最大帽檐 Ø mm
	N	(kp)	N	(kp)		
3	1.000	(102)	1.300	(133)	1,95	6,5
3,2	1.200	(122)	1.500	(153)	2,0	6,5
4	2.000	(204)	2.500	(255)	2,5	8,0
4,8	2.900	(296)	4.000	(408)	3,0	9,5
5	3.100	(316)	4.400	(449)	3,0	9,5
6	4.400	(449)	6.000	(612)	3,65	12,0
6,4	4.900	(500)	6.800	(694)	3,85	13,0

测试程序按照 DIN EN ISO 1458 9标准

色彩图例



铝



钢



铜



A2 不锈钢



蒙乃尔



塑料



A4 不锈钢

作为德国GESIPA® 中国区重要合作伙伴，我们愿携手GESIPA® 公司共同为中国区客户提供高质量铆接解决方案。